







■ DATA SHEET PROPORTIONER FD2000 GEN III FOR STATIONARY EXTINGUISHING SYSTEMS.



■ 1. TECHNICAL DATA.

Type		FD2000/0.5-S EV	FD2000/1-S EV	FD2000/3-S EV	FD2000/3/3-S EV
Proportioning rate		0.5 %	1 %	3 %	3% + 3% = 6%
Approvals ¹⁾	FM	–	 FM Approval PR463231	–	–
	DNV	 TAF00000GK			
	VdS	–	–	 G420028	–
Flow directions of water motor		Horizontal: "left → right" or "right → left" Vertical: "top → bottom" or "bottom → top"			
Min. water flow rate ²⁾		180 l/min		200 l/min	280 l/min
Min. water flow rate FM		–	270 l/min	280 l/min	–
Max. water flow rate		2000 l/min			
Operating temperature ³⁾		5° C – 50° C (standard version) 5° C – 80° C (High-Temp version) ^{x)}			
Storage temperature		-20 °C – 80 °C			
Operating pressure		5 – 16 bar			
Weight ⁴⁾					
Freshwater version		57 kg	58 kg	80 kg	121 kg
Seawater version ^{x)}		102 kg	103 kg	125 kg	166 kg
ATEX classification ^{x)} for +5 °C ≤ T_a ≤ +60 °C		 			

1) Information regarding FM Approved data, please refer to www.approvalguide.com. For DNV Approval conditions, see DNV Certificate TAF00000GK. For VdS Approval conditions, see VdS Certificate G420028.

2) The nominal proportioning rate is achieved when reaching the specified minimum figure. Indication for proportioning of fluid Newtonian foam agents at operating pressure of 5 bar. For more detailed information, refer to page 2 and 3, item 3. "Minimum water flow rate".

3) Operating temp. is the max. ambient and medium (foam and extinguishing water) temperature. Max. foam agent temp. is generally limited to 50 °C.

4) Weight indications are based upon the standard version in dry condition. Special versions will differ.

X) Optional equipment.




1 / 6



www.firedos.com



■ 2. PRESSURE LOSS.


Indication valid for operating pressure of 10 bar. For more information on different system conditions or proportioning rates, please contact us.



■ 3. MINIMUM WATER FLOW RATE.


The following diagrams show the effect of the operating pressure and foam agent viscosity on the minimum water flow rate (valid for viscosities in the graph at para. 4). The values can be reduced to approx. 35% by an optional flow reduction. The values increase by approx. 40% in the high-temp version. For values at other proportioning rates, please contact us.





■ 4. FOAM AGENT VISCOSITY.

FireDos proportioners are suitable for all foam agents available on the market. For reference regarding units with an FM Approval, please find the corresponding/associated range of dynamic viscosity below (www.approvalguide.com). Contact us if the dynamic viscosity of your foam agent is higher than the values in the diagram. **Do not hesitate to request our support for the correct dimensioning of your suction line.**




5. MATERIALS.

	Freshwater version	Seawater version
Water motor ⁵⁾	Cast Aluminium G-AlSi7Mg HC-coated, AlMgSi1 HC-PTFE-coated, stainless steel 316 / 316Ti, POM, PVDF, NBR, FKM	Cast Bronze G-CuSn10, stainless steel 316 / 316Ti, Aluminium-Bronze CuAl10Fe5Ni5-C-GC, POM, PVDF, NBR, FKM
Proportioning pump ⁵⁾	Stainless steel 316 / SS316Ti / 318 LN, POM, FKM, Aluminium oxide ceramic Al ₂ O ₃ , Aluminium-Bronze CuAl10Ni5Fe5-C-GC, PEEK	
Pipework ⁵⁾	Stainless steel 316 / CF8M / SS316Ti, PTFE, FKM	
Air bleed ⁵⁾	Stainless steel 316 / CF8M / SS316Ti, PTFE, brass	Stainless steel 316 / CF8M / SS316Ti, PTFE
Support frame	Stainless steel 304 / 316	


⁵⁾ media-exposed materials

6. FLOW DIAGRAM.

Proportioning rate 0.5% / 1% / 3%




Proportioning rate 3% + 3% = 6%



- | | |
|--|---|
| 1. Water motor | 12.1 "Returning / Proportioning" pump head I |
| 2. Proportioning pump | 12.2 "Returning / Proportioning" pump head II |
| 3. Coupling | 13. Check valve in the proportioning line |
| 4. 2-way ball valve "Flushing / Priming" | 14. Pulsation damper y) |
| 4.1 "Flushing / Priming" pump head I | 15. Standard scope of supply of FireDos proportioner |
| 4.2 "Flushing / Priming" pump head II | 16. Revolution counter with flow rate display x) |
| 5. Filter in the flushing line | 17. Flow meter for return line x) |
| 6. Check valve in the flushing line | 18. Pressure sustaining valve for return line x) |
| 7. Check valve in the suction line | 19. 2-way ball valve in return line x) |
| 8. Air bleed valve | 20. Foam agent supply |
| 9. Air bleed hose | 21. Shut-off valve in the suction line |
| 10. Shut-off valve pressure gauge | 22. Extinguishing water supply |
| 11. Pressure gauge | 23. Water filter |
| 12. 3-way ball valve "Returning / Proportioning" | |
- X) Special version y) not applicable

7. EXAMPLE FIGURE / DIMENSIONS.



Type	FD2000/0.5-S EV	FD2000/1-S EV	FD2000/3-S EV	FD2000/3/3-S EV
Proportioning rate	0.5 %	1 %	3 %	3% + 3% = 6%
Connection water motor A	Optionally: - 4" MT BSP, 3" FT BSP (Standard) - Flange acc. DIN EN 1092-1, DN100 PN16 RF - Flange acc. ASME B16.5, 4" Class 150 RF			
Installation length water motor X ⁶⁾	452 mm			
Connection suction line B	1¼" MT BSP or 1¼" MT NPT ^{X)}		2" MT BSP or 2" MT NPT ^{X)}	2x 2" MT BSP or 2x 2" MT NPT ^{X)}
Connection return line C	½" FT BSP or ½" MT NPT ^{X)}	¾" FT BSP or 1" MT NPT ^{X)}	1" FT BSP or 1" MT NPT ^{X)}	2x 1" FT BSP or 2x 1" MT NPT ^{X)}
Length L ⁶⁾	865 mm	885 mm	980 mm	1050 mm
Width W ⁶⁾	505 mm	505 mm	600 mm	750 mm
Height H ⁶⁾	425 mm	445 mm	480 mm	565 mm

All figures are approximate only and depend on the particular version / equipment options.

X) Special version.

6) Further accessories to the proportioner may require more installation space.

Please allow sufficient accessibility of the proportioner for maintenance work. For assistance to ensure sufficient accessibility, please refer to our planning manual for proportioners.

8. MANUFACTURER.

FireDos GmbH, Auf der Kaulbahn 6, 61200 Woelfersheim, Germany
Phone +49 (0) 6036 9796-0, Email: info@firedos.de

We reserve the right to make modifications at any time.