

LUKAS	eDRAULIC Cutter			EN
	S 378 e3 92-20-24			
	Technical Data			
<i>Non-metric dimensions are for reference only.</i>				
Nomenclature		Value	Unit	Remark
Dimensions	L x W x H	846 x 235 x 253 33.3 x 9.25 x 9.96	mm in.	closed; w/o battery
Weight		17,8 39,249	kg lbs.	incl. hydraulic fluid, w/o battery
Weight battery 9 Ah		1,6 3,528	kg lbs.	
Weight battery 5 Ah		1,2 2,646	kg lbs.	
Rechargeable battery 1 / 2		25,2 5,0 / 9,0	V DC Ah	Li-Ion, optional accessory
Current consumption		8 45	A A	idle mode max. load
Ambient temperature		-20 ... +55 -4 ... +131	°C °F	
Opening / closing time	>	2	s	w/o load
Cutting performance		Ø33 Ø1.30	mm in.	acc. to EN 13204 / NFPA 1960
Opening width at tips		202 7.99	mm in.	at tips
Operating pressure		70 10,000	MPa psi	
Noise pressure level		75	dB(A)	acc. to EN 13204
Sound power level		90	dB(A)	acc. to EN 13204
EN 13204 Cutting performance		1I-2J-3K-4J-5J		
Protection class DIN EN 60529:2014-09		IP 58		Up to 60 minutes and a depth of up to 3 meters
Note:				
Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.				
LUKAS Hydraulik GmbH		Weinstraße 39 • D-91058 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394		

Änderungen vorbehalten / Subject to revision