

LUKAS	eDRAULIC Spreader			EN
	SP 777 e3 Connect 93-15-31			
	Technical Data			
<i>Non-metric dimensions are for reference only.</i>				
Nomenclature		Value	Unit	Remark
Dimensions	L x W x H	997 x 309 x 253 39.3 x 12.2 x 9.96	mm in.	closed; w/o battery
Opening width at tips		813 32.0	mm in.	
Force / spreading	min.	63 14160	kN lbf.	25 mm from front end of tips
Force / spreading	max.	600 134900	kN lbf.	
Force / pulling	max.	60 13490	kN lbf.	with chain set KSV 11
Pulling distance		655 25.8	mm in.	with chain set KSV 11
Ambient temperature		-20 ... +55 -4 ... +131	°C °F	
Weight		23,4 51.6	kg lbs.	incl. hydraulic fluid, w/o battery
Weight battery 9 Ah		1,6 3.6	kg lbs.	
Weight battery 5 Ah		1,2 2.7	kg lbs.	
Protection class DIN EN 60529:2014-09		IP 58		Up to 60 minutes and a depth of up to 3 meters
Opening / closing time	>	2	s	w/o load
Noise pressure level	idle mode max. load	68 74	dB(A) dB(A)	nach EN 13204 nach EN 13204
Rechargeable battery 1 / 2		25,2 5,0 / 9,0	V DC Ah	Li-Ion, optional accessory
Current consumption		7 43	A A	idle mode max. load
Operating pressure		70 10,000	MPa psi	
Note: Since all values are subject to tolerances, minor differences may occur between the data of your equipment and this data.				
LUKAS Hydraulik GmbH Weinstraße 39 • D-91013 Erlangen • Tel.+49 9131/698-0 • Fax +49 9131/698-394				